

PROGRAMMABLE MULTI-STANDARD CB TRANSCEIVER  
USABLE IN ALL THE EUROPEAN COUNTRIES

M-899 VOX

MULTISTANDARD  
9 BANDS PROGRAMMABLE  
FOR USE IN ALL THE  
EUROPEAN COUNTRIES  
LARGE SIZE BLUE COLOR  
BACKLIGHTED LCD  
VOX FUNCTION WITH  
ADJUSTABLE VOX GAIN  
MANUAL OR FIXED SQUELCH  
RF GAIN CONTROL  
BACKLIGHTED RUBBER KEYS  
EXTERNAL EARSET JACK  
EXTERNAL MIC JACK  
REMOTE PUSH-TO-TALK  
INCLUDED  
EXTERNAL EARSET-MIC  
WITH DUAL JACK  
INCLUDED  
DUAL CHANNEL AND 5-DIGIT  
FULL FREQUENCY READOUT  
DIGITAL S/RFBAR METER  
ROTARY CHANNEL CONTROL  
PA, EMG, ANL  
EXTRA SOFT  
MICROPHONE  
CORD

# SAFE DRIVE RADIO !

CONVENIENT REMOTE PTT CONTROL AND EXTERNAL  
EARSET-MICROPHONE INCLUDED !  
REAL HANDSFREE OPERATION IN **VOX MODE**

INCLUDED !



REMOTE PUSH-TO-TALK CONTROL WITH  
CURL CABLE AND VELCRO STRAP FIXING

INCLUDED !



EXTERNAL EARSET-MICROPHONE WITH  
DUAL JACK, FOR HANDSFREE OPERATION



feature  
**PACKED**  
see reverse for full details

## SAFE DRIVE RADIO

CONVENIENT REMOTE PTT  
CONTROL AND EXTERNAL  
MICROPHONE INCLUDED !

KEEP YOUR HANDS ON  
THE STEERING WHEEL  
WHILE DRIVING !

**3 OPERATING MODES FOR TRANSMITTING !  
3 OPERATING MODES FOR RECEIVING !**

(SEE REAR SIDE FOR FULL DETAILS)



**INTEK**

**ACCESSORIES  
ARE INCLUDED !**



**3 OPERATING MODES FOR TRANSMITTING !**

**PTT (PUSH-TO-TALK) WITH STANDARD MICROPHONE**



**PTT (PUSH-TO-TALK) WITH HANDSFREE MICROPHONE AND REMOTE PTT CONTROL**



**FULL HANDSFREE ! WITH HANDSFREE MICROPHONE AND VOX FUNCTION**



**3 OPERATING MODES FOR RECEIVING !**

**LISTEN FROM THE BUILT-IN SPEAKER**



**LISTEN FROM THE EXTERNAL EARSET**



**LISTEN FROM AN EXTERNAL SPEAKER (OPTIONAL)**



*the ultimate mobile radio from the world leader in CB transceivers !*

**SAFE DRIVE RADIO**

**CONVENIENT REMOTE PTT CONTROL AND EXTERNAL MICROPHONE INCLUDED !**

**KEEP YOUR HANDS ON THE STEERING WHEEL WHILE DRIVING !**

**SPECIFICATIONS GENERAL**

Modes (AM, FM) As per selected band  
Operating Temp. -10°/+55°C  
DC Input Voltage 13.2Vdc ±15%  
Size / Weight 153(L) x 50(H) x 185(D) mm / 750 gr.

**RECEIVER**

System CPU Controlled Double Conversion Super Heterodyne  
IF 1° 10.695 MHz / 2° 455 KHz  
Sensitivity 0.5µV for 20dB SINAD (FM)  
0.5µV for 20dB SINAD (AM)  
Audio Output Power @ 10% THD 2.5W at 8 Ohm  
Image Rejection 65dB  
Adjacent Ch. Rejec. 65dB  
Current Drain 350mA (stand-by)

**TRANSMITTER**

System CPU Controlled PLL Synthesizer  
Max Output Power 4W at 13.2Vdc  
Modulation AM (85% to 90%)  
FM (1.8 KHz ±0.2 KHz)

Output Impedanced 50 Ohm unbalanced  
Current Drain 1300 mA (at no modulation)

**FREQUENCY BAND / MODE PROGRAM (CE / R&TTE VERSION)**

**E1** ITALY/SPAIN 40CH AM/FM 4W  
**I2** ITALY 36CH AM / FM 4W  
**dE** GERMANY 80CH FM 4W / 12CH AM 1W  
**d2** GERMANY 40CH FM 4W / 12CH AM 1W  
**EU** EUROPE/FRANCE 40CH FM 4W / 40CH AM 1W  
**CE** CEPT 40CH FM 4W (DEFAULT)  
**U** ENGLAND 40CH + CEPT 40CH FM 4W  
**PL** POLAND 40CH AM/FM 4W (-5 KHz)  
**Pd** POLAND 40CH AM 1W / FM 4W (-5 KHz)

**FREQUENCY BAND / MODE PROGRAM (INT'L VERSION)**

**RU** WIDE BAND 25615-30105 KHz 450CH AM/FM 4W  
**PO** WIDE BAND 25610-30100 KHz 450CH AM/FM 4W  
**C2** 26830-27405 KHz 43CH FM 4W  
**S** WIDE BAND 26515-27855 KHz 120CH AM/FM 4W  
**P2** WIDE BAND 26510-27850 KHz 120CH AM/FM 4W

E. & O. E.



**CB 27 MHz  
CAR & TRUCK  
MOBILE ANTENNAS**

